

Conditions of Acceptability:

Use - For use only in (or with) complete equipment where the acceptability of the combination is determined by UL LLC.

1. Rated output loading for these products was achieved using electronic loads.
2. During the temperature test of the end product, the temperature at Tc is to be monitored. The absolute value at Tc shall not exceed 90°C.
3. These products are intended for building in. The case for these products have no openings. Acceptability of the LED driver with respect to mounting, enclosure, spacing, casualty, temperature and segregation is to be determined as part of the end device evaluation.
4. These products are provided with 18 AWG, stranded, rated 105°C, 300V minimum for input and min. 22 AWG for LED Class 2 output/dimming connections. Acceptability of the lead wire being smaller than 18 AWG is to be determined as part of the end product evaluation.
5. These products have multiple outputs. Interconnection of these outputs has been evaluated. Acceptability of interconnection of these outputs (and the associated circuits) is to be considered as part of the end product evaluation.
6. These products are dimmable using a low voltage 0-10 V. This interface is a source, since the product provides the source of supply for the interface. The interface circuit has been evaluated for isolation from primary (input) and secondary (output) circuits with spacing based on the maximum rated branch supply, 277 Vac.
7. These products are marked suitable for dry/damp locations. Additional considerations will be necessary if these products are integrated into wet rated end devices (i.e. input and output supply connection means, accessibility of the output based on maximum voltage restrictions for wet rated Class 2 circuits, acceptability of markings, etc.).
8. Based on maximum voltage restrictions for Class 2 circuits in the Canadian Electrical Code, the output cannot be accessible. The output terminals of the end product should be evaluated to confirm compliance with this accessibility requirement, either based on output terminal design or based on manufacturer specifications for its use in restricted access areas only. The latter option will require markings on the end product as well as the installation manual.