

LED55WPRT5 Series – Programmable LED Driver Built-In Step-Dimming Control 0-10V Dimmable Constant Current Driver Narrow cross-section fits T5-style ballast channels

Electrical Specifications

Input Voltage Range:	120-277 Vac Nom. (108-305 V Min/Max)	
Frequency:	50/60 Hz Nom. (47-63 Hz Min/Max)	
Power Factor:	≥ 0.90 @ ≥ 50% load, 120/230Vac; 65% load, 277Vac	
Inrush Current:	< 30.0 Amps max @ 277 Vac	
Input Current (Max):	0.56 Amps @ 120 Vac, 60Hz 0.25 Amps @ 277 Vac, 60Hz	
Maximum Power:	55W	
Line Regulation:	±3%	
Load Regulation:	±4%	
THD:	\leq 20% @ \geq 50% load, 120/230Vac; 65% load, 277Vac	
Ripple Current:	4% (Max)	
Start-up Time:	500mS typical	
Output Protection:	Over-Voltage, Over-Current, and Short Circuit Protection with Auto Recovery	

Environmental Specifications

Maximum Case Temp.	80°C
Type TL Rating:	90°C/ 68°C
Minimum Starting Temp:	-30°C
Storage Temperature:	-40°C to +85°C
Humidity:	Up to 90% RH
Cooling:	Convection
Vibration Frequency:	5 to 55 Hz/2g, 30 minutes
Sound Rating:	Class A
Lifetime:	50,000 Hours, 68°C @ Tc point (see graph for details)
MTBF:	352,000 hours @ Full Load per MIL-217F Notice 2
EMC:	FCC 47CFR Part 15 Class A compliant



- Dim to zero with 0-10V dimming
- Metal housing

Constant Current - Product Specifications					
Model Number	Output Current (mA ±5%)	Output Voltage (Vdc)	Max Output Power (W)	Type TL Rating	Typical Efficiency
LED55WPR1T5-055-C1500-D5	100-1500	12-55	55	90/68°C	88%

Class 2: US/Canada



Note:

LED drivers are designed and intended to operate LED loads only. Non-LED loading may be outside the specified design limits of our LED drivers, and therefore cannot be covered by any warranty. If you desire to use our LED drivers to operate non-LED loads please contact us to discuss compatibility.

Specifications subject to change without notice.

Rev 8-31-16





SSL Solutions Faster Than The Speed Of Light®

Pg 2 of 5





SSL Solutions Faster Than The Speed Of Light®

Pg 3 of 5



Step Dimming Logic

SW1	SW2	lout	Pin
Open	Open	0%	0% (OFF)
Open	Closed	40%	<50%
Closed	Open	40%	<50%
Closed	Closed	100%	100%

Step Dimming Notes:

1. Bi-level output is controlled with standard wall switches.

 Programmable output current must be set to a minimum of ≥ 700mA for step-dimming to function.

0-10VDC Dimming

Parameters	Minimum	Typical	Maximum
Source Current out of 0-10V Purple Wire	0 mA		1.5 mA
Absolute Voltage Range on 0-10V (+) Purple Wire	-2.0 V		+15 V

Typical Dimming Circuit: 2-Wire Resistance



Typical Dimming Circuit: 2-Wire 0-10V Analog



0-10V Dimming Notes:

- 1. Part comes with two dimming input connectors +Purple/-Gray on the output side.
- 2. Part is compatible with most 0-10V Wall Slide dimmers and direct 0-10V analog signal.
- 3. Output current will be 0% when Vdim ≤0.60V. This is dim to zero operation.
- 4. Output will be 100% with Purple/Gray open zand 0% with Purple/Gray Shorted.
- Dimming leads are isolated from input leads. Dimming leads are not isolated from output leads. Always shut off power at circuit breaker when working on electrical connections.

Labeling Programmable Drivers:

It is highly recommended that the drivers be labeled with information traceable to the programming profile. It can include the programmed output current, dimming curve type, minimum dimming level and name of the file storing the profile. *This information is critical to answering any field questions from the contractor or end user.*

Output Current / 0-10VDC Dimming Control Voltage lout Min set to 0%





SSL Solutions Faster Than The Speed Of Light®

Pg 4 of 5





Rset Resistor Rating: $\geq 1/4W$, $\pm 1\%$ tolerance, $\geq 20V$ rating

Safety Certification	Standard
UL/CUL	UL8750, UL1310 for UL Class 2 & CAN/CSA C22.2 No. 250.13, UL Type TL 90/68°C
CE	EN61347-1, EN61347-2-13
EMC Standard	Notes
FCC, 47CFR Part 15	Class A
EN 55015	Limits and methods of measurement of radio disturbance characteristic of electrical lighting and similar equipment.
EN 61000-3-2	Part 3-2: Limits for harmonic current emissions Class C, ≥80% Rated Power
EN 61000-3-3	Part 3-3: Limitation of voltage changes, voltage fluctuations and flicker.
EN 61000-4-5	Part 4-5: Surge Immunity test, 2 kV L-N, 4 kV L-FG & N-FG
Energy Star	Energy Star transient protection: Ballast or driver shall comply with ANSI/IEEE C62.41.1-2002 and ANSI/IEEE C62.41.2-2002, Category A operation. The line transient shall consist of seven strikes of a 100 kHz ring wave, 2.5 kV level, for both common mode and differential mode.



Rset Table (nominal output currents)

Rset (Ω)	lout (mA)
100	100
162	130
230	160
270	180
320	200
395	230
442	250
569	300
698	350
845	400
996	450
1150	500
1490	600
1870	700
2300	800
2800	900
3320	1000
3660	1050
5230	1250
5700	1300
6220	1350
6800	1400
7460	1450
8200	1500
9000	1500



SSL Solutions Faster Than The Speed Of Light®

Pg 5 of 5

Module Temperature Protection using External NTC (Negative Temperature Coefficient)

NTC

Select a Negative Thermal Coefficient (NTC) resistor with a resistance range that allows the full output current to flow at safe LED operating temperatures.

NTC resistance should drop sufficiently to allow reduced output current at elevated or harmful LED temperature levels. NTC operation should be thoroughly tested to ensure proper operation over all the full temperature range of the Driver and the LED Engine.

Factory settings:

NTC Minimum Ohms = 2.0KNTC Minimum Level (%) $\simeq 0\%$ lout, NTC Maximum Ohms = 3.2K, 100% lout



Module Temperature Protection Example

NTC = 805SMD, R_{25C} = 15K Ohm ± 2%, R_{64C} = 3700, Vishay Part #: NTCS0805E3153GMT Default Settings: NTC Max = 3.0K, NTC MIN = 2.0K, Iout Min = 10%



Note:

Disconnect power to LED driver for at least 30 seconds before connecting or disconnecting Driver output and LED Engine. This prevents potential arcing transients that can damage the Engine and Driver. See Hot Plugging in our Driver Application Guide for more information.